

# Butyl Caulk

Butyl Caulk is a high solids butyl rubber compound designed to meet the requirements of Federal Spec TTS-001657 and A-A-272 Type III.

## Features

- Non-sagging
- Paintable
- Water Resistant
- High Solids
- Meets LEED® Requirements

## Seals and Bonds

Wood, Glass, Plastic, Concrete and Metals

## Technical Data

Color	Gray, Black, White and Custom Colors Available
Solvent	Aliphatic Hydrocarbons
Weight	12.0 lbs. per Gallon [1438 g per Liter]
Solids Content	85% (+/-2%)
Yield Strength	24 Hours @ R.T. = 6.9 CORES
Elongation	54%
Service Temperature	-40° to 250°F [-40° to 121°C]
Chemical Resistance	Excellent to Water and Mild Acids
VOC	189 g per Liter

## Additional Specifications

U.S.D.A Acceptability: Product meets the U.S.D.A. requirements for use in meat and poultry processing areas under U.S.D.A. inspection.

F.D.A. Acceptability: Meets 21CFR175.105 requirements

## Application

Temperature	Above 40°F [4°C]
Method	Standard Caulking Gun
Preparation	Clean Dry Surface with Adequate Ventilation
Clean-up	Clean Tools with Mineral Spirits
Disposal	According to Local, State and Federal Laws
Painting	Can be Painted After Full Cure

## Storage

Temperature	Moderate Conditions
Shelf Life	18 Months