

Perma-Kote™

Roof Coating

Perma-Kote™ Roof Coating is ideal for galvanized metal and EPDM rubber roofing sealant and protection. Perfect for RV and Marine applications where absolute protection is needed. Perma-Kote™ is a self-leveling, co-polymer roof coating and seam sealer designed for ozone and ultra violet resistance.

Features

- Ultraviolet Resistant
- Quick Cure
- Water Resistant
- Self-leveling

Seals and Bonds

Most Roofing Surfaces, RV and Marine Applications

Technical Data

Color	White (Custom Colors Available, 50 Gallon Min. [190 L])
Solvent	Aromatic Hydrocarbons
Weight	7.5 lbs. per Gallon [898 g per Liter]
Solids Content	44 – 46% (+/-2%)
Viscosity/Rheometer	10,000 – 12,000 cps @ 78°F [26°C]
Elongation	300%
Service Temperature	40° to 90°F [4° to 32°C]
Exposure Range	-20° to 250°F [-20 to 121°C]
Cure Rate	24 Hours @ 0.062" [2 mm] Thick
ASTM D510 (%)	0.13
VOC	434 g per Liter

Application

Temperature	Above 40°F [4°C]
Preparation	Apply to a Clean Dry Surface
Disposal	According to Local, State and Federal Laws

Storage

Temperature	Moderate Conditions
Shelf Life	1 Year