



777 Sealant

Permatite® 777 Sealant is an Acrylic Latex that is U.L. Classified. Seals low, medium, high pressure and high velocity HVAC duct systems. With excellent adhesion to galvanized metal, 777 cures to a tough flexible film.

Seals & Bonds

Galvanized metal, fiberglass, duct board and flex duct

Technical Data

Color	Gray
Weight per Gallon	11.4 Lb.
Solids Content	73% (+/-2)
Service Temperature	-40°F to +200°F
U.L. Classified	

Pressure Rating

777 Sealant is recommended for use in HVAC duct systems, which do not exceed 16" water column pressure.

Additional Specification

Underwriters Laboratories Inc.
Classified: Caulkings and Sealants
Surface Burning Characteristics

Applied to Inorganic Reinforced-Cement Board+	
Flame Spread	5
Smoke Developed	0

+ Tested as applied in two 1/4 in. wide strips 8 in. on center and covering 2.5 percent of the test sample area.



Sizes

Stock No.	Package Size	Case Pack
DS18160	10.3 oz.	24
DS18162	1 Gallon	4

- WATER BASED
- U.L. CLASSIFIED
- USE INDOORS & OUTDOORS
- FAST CURE
- NO HARMFUL FUMES


Application

Temperature	Above 40°F
Method	Standard caulking gun
Preparation	Apply to clean dry surface. Adequate ventilation required.
Clean Up	Clean tools with soap and water.
Disposal	According to Local, State and Federal Laws
Cure Time	12-24 hours depending on temperature, humidity and application.
Painting	Can be painted after full cure.

Storage

Temperature	Moderate conditions
Shelf Life	1 Year

For additional information Contact:



14551 Judicial Rd., Suite 115 · Burnsville, MN 55306

Phone: (952) 898-3200

Fax: (952) 898-3232

info@permatite.com

www.permatite.com