



**Permatite® 8000** is a self-leveling single component elastomeric sealant designed specifically for RV and Mobile Home maintenance and repair. Excellent resistance to moisture, mildew and ozone.

### Seals & Bonds

EPDM, PVC, wood, aluminum and galvanized metal.

### Technical Data

Color	White, Aluminum
Solvent	Aromatic Hydrocarbons
Weight per Gallon	7.5 Lb.
Solids Content	55% (+/-2)
Viscosity	85,000 cps Brookfield #6 @ 20 rpms / 78°F
Service Temperature	-45°F to +250°F
Elongation	300%
Vapor Transmission	0.13

### Sizes

Stock No.	Package Size	Case Pack
DS24201	10.3 oz.	24
DS24205	5 Gallon	1

### • EXCELLENT ADHESION TO RUBBER ROOFING

### • S/B - SELF-LEVELING

### • FAST SKIN OVER

### • ULTRA VIOLET RESISTANT

### Application

Temperature	Above 40°F
Method	Standard caulking gun
Preparation	Apply to clean dry surface. Adequate ventilation required.
Clean Up	Clean tools with mineral spirits.
Disposal	According to Local, State and Federal Laws
Painting	Can be painted after full cure.

### Storage

Temperature	Moderate conditions
Shelf Life	1 Year

For additional information Contact:

**Permatite®**

14551 Judicial Rd., Suite 115 · Burnsville, MN 55306

Phone: (952) 898-3200

Fax: (952) 898-3232

info@permatite.com

www.permatite.com