



Permatite® Acrylic Sealant is a 100% elastomeric acrylic water based caulk, which is designed to meet the standards of ASTM C-920 and remain tough, flexible, rubbery and weather-resistant for many years. **Permatite®** Acrylic Sealant has also been designed to exhibit excellent bonding and adhesive properties in most construction applications.

Seals & Bonds

Metals, wood, plywood, sheeting, wallboard and flexible foams.

Technical Data

Color	Gray	
Weight per Gallon	13.25 Lb.	
Solids Content	84% (+/-2)	
Service Temperature	0°F to +200°F	
Specific Gravity	1.58	
ASTM C-920	Class 25	
Elongation @ Break	1,000	
Max Tensile (psi)	40	
ASTM C-719	Glass	Pass
	Aluminum	Pass
Hardness, Shore A	17	

Additional Specifications

U.S.D.A. Acceptability	Product meets the U.S.D.A. requirements for use in meat and poultry processing areas under U.S.D.A. inspection.
F.D.A. Acceptability	Meets 21CFR175.105 requirements
Mil Spec	Meets TTS-001657 A-A-272 Type III

Sizes

Stock No.	Package Size	Case Pack
DS18150	10.3 oz. Cartridge	24

- WATER BASED
- SOLVENT FREE
- FAST SKIN OVER
- NON-SAGGING
- HIGH SOLIDS

Application

Temperature	Above 40°F
Method	Standard caulking gun
Preparation	Apply to clean dry surface. Adequate ventilation required.
Clean Up	Clean tools with soap and water.
Disposal	According to Local, State and Federal Laws
Cure Time	12-24 hours depending on temperature, humidity and application.
Painting	Can be painted after full cure.

Storage

Temperature	Moderate conditions
Shelf Life	1 Year

For additional information Contact:

Permatite®

14551 Judicial Rd., Suite 115 · Burnsville, MN 55306

Phone: (952) 898-3200

Fax: (952) 898-3232

info@permatite.com

www.permatite.com