



Permatite® Butyl Caulk meets federal specifications **TTS-001657**. This is a one-part butyl rubber sealant composed of elastomeric hydrocarbons, blended with suitable pigments, oxidation and UV absorbent to qualify as a high quality architectural caulk. After full cure, it remains flexible for a permanent and watertight seal.

Seals & Bonds

Wood, glass, plastics, concrete and metals

Technical Data

Color	Gray, Black, White
Solvent	Aliphatic Hydrocarbons
Weight per Gallon	12.0 Lb.
Solids Content	85% (+/-2)
Service Temperature	-45°F to +250°F
Elongation	54%
Chemical resistance	Excellent to water and mild acids
Meets Federal Spec	TTS-001657 A-A-272 Type III

Sizes

Stock No.	Package Size	Case Pack
DS11152	10.3 oz. cartridge	24
DS11154	1 Gallon	4
DS11155	5 Gallon Pail	1

- **WATER RESISTANT**
- **ULTRA VIOLET RESISTANT**
- **QUICK TACK**
- **NON-SAGGING**
- **PAINTABLE**

Application

Temperature	Above 40°F
Method	Standard caulking gun
Preparation	Apply to clean dry surface. Adequate ventilation required.
Clean Up	Clean tools with mineral spirits.
Disposal	According to Local, State and Federal Laws
Painting	Can be painted after full cure.

Storage

Temperature	Moderate conditions
Shelf Life	1 Year

For additional information Contact:

Permatite®

14551 Judicial Rd., Suite 115 · Burnsville, MN 55306

Phone: (952) 898-3200

Fax: (952) 898-3232

info@permatite.com

www.permatite.com