



Permatite® C-I Duct Sealer is a one part fire retardant elastomeric-based compound, combined with elastomeric hydrocarbons and adhesion promoters. Designed especially for sealing most types of medium or high-pressure ventilation systems.

Seals & Bonds

Galvanized metals, aluminum, plastics and fiberglass.

Technical Data

Color	Gray
Solvent	Aromatic Hydrocarbons
Weight per Gallon	12.1 Lb.
Solids Content	72% (+/-2)
Viscosity	90 seconds/ .104 orifice, 40 psi @ 78°F
Service Temperature	-45°F to +200°F
Flame Spread	10
Fuel Contribution	0
Smoke Density	50
NFPA Class	A
UBC Class	I

Sizes

Stock No.	Package Size	Case Pack
DS19160	10.3 oz.	24
DS19164	1 Gallon	4
DS19165	5 Gallon	1
DS19166	50 Gallon	1

- **MEETS ASTM-E84**
- **FIRE RETARDANT CURED**
- **NON-SAGGING**
- **HIGH PERFORMANCE**

Application

Temperature	Above 40°F
Method	Standard caulking gun
Preparation	Apply to clean dry surface. Adequate ventilation required.
Clean Up	Clean tools with mineral spirits.
Disposal	According to Local, State and Federal Laws
Painting	Can be painted after full cure.

Storage

Temperature	Moderate conditions
Shelf Life	1 Year

For additional information Contact:

Permatite®

14551 Judicial Rd., Suite 115 · Burnsville, MN 55306

Phone: (952) 898-3200

Fax: (952) 898-3232

info@permatite.com

www.permatite.com